

Fig. 3

< m $oldsymbol{\Sigma}$ § **1** ^ M454:3 🔷 💲 🔃 0 Up Manufocturing Panel
direction 0.300 < Board step (standard is .3") Internet 6 GO TO SAVED 0.001 Annular Ring (Inner Layers) 0.002 Annular Ring (Outer Layers) 226 CLEAR ALL PRINT <<Symmetric Construction of Multi-Layer Recommended Profile Tolerance
 371.25 Sq. In. / Monufacturing Panel (22.5 X 16.5) 2 Option SAVE /COMPARE 1 Option 3 Option Min. Pad Size (Outer)
 Outer Layer Hale Tolerance
 Min. Pad Size (Inner)
 Inner Layer Hole Tolerance 3.1:1 Aspect Ratio < Panel border Y direction 506 < Holes < or = 0.020" Fixtures/ Tooling Retail Price/ Board \blacksquare ~202 208 ~208 204 \$0.00 \$0.00 Assistant Tools Bare Board */-.010 >=.002 HASL (Hot Air Solder Leveled) >=.003 Length 0.500/0.500 & Favorites standard 🔁 Bare Board Design Assistant – Microsoft Internet Explorer 0.750 ŧ Min. Finished Plated Through Hole (Outer Layer) Plated Thru Hole Prep.
Min. Finished Plated Through Hole (Inner Layer)
Moximum Finished Plated Through Hole (Inner Layer)
Enter Total * Different Through Hole Sizes
Enter Total * Different House / Board Annular | Search Panel border X direction (standard is .75") 2088 208 Bare Board Design Assistant Finished Board Thickness (inches) / Tolerance Select Ounces of Finished Copper (Outer Layers) Select Ounces of Copper (Inner Layers) Select Surface Finish over Copper Set Monitor to 1024 x 768 Pixels Monitor 200M Annular Manufacturing Panel UtilizationX (Calculated)
Number of Boards Manufacturing Panel (Calculated) Bare Board Des... Help \$ ■ Hold Curser over a question for description ■ Tools Single Board or Multi-Board Array? (3) Design 1,1

×

①

Bock

Address

Þ

Ŀ

File Edit View Favorites

Fig. 4

Are there any Plated Slots?

Bstart

6

Select Laminate Material Enter Quantity Turnaround Required? Select type of Board



| are Board Design Assistant - Microsoft Internet Explorer | X |
|---|-------------|
| File Edit View Forentles Tools Help | B |
| ← Bock • → X Z ← X Z Covorthes C Wedio ← Ø ♥ ♥ □ Links | |
| S Address Address | ဒ |
| | |
| Design Assistant Tools | < an |
| Bare Board | |
| | <u>></u> |
| SAVE /COMPARE | 4 |
| \$0.00 Retail Price/ | |
| Bodrd C. Spirott | |
| Sinia Book | |
| Width | |
| Proc. /+ | |
| Manufacturing Panel Willianthank (Calculated) 75% 371.25 Sq. In./Manufacturing Panel (22.5 X 16.5) Mumber of Beards / Manufacturing Panel | |
| 75") < Panel border Y | |
| (* | |
| , P | |
| erance 7 | |
| Select Ounces of Copper (Inner Layers) 1 Wests Select Surface Flight over Copper | |
| (Outer Lover) • 0.0197 0.037 | |
| standard >=.003 < Outer Layer Hole Tolerance | |
| | |
| Sizes | |
| Are there ony Blatad Stots? Ring on No | • |
| | |
| Done & Internet | |
| (Bstart) ■ Bare Board Design As | 7AN |
| | 7 |

Fig. 5




Fig. 6

2,200

| 8 Bare Board Design Assistant - Microsoft Internet Explorer | st Explorer | | |
|---|--|---|--------------|
| file Edit View Favorites Tools Help | | | B |
| ← Book • → X 🗷 🐔 🗘 D Search 🎌 Favoriles | ₹Favorites & Media € 🖄 🕾 | sylin R | |
| Address | | TO Principle | ° ♠ `^ |
| | | | |
| Design Assist | Assistant Tools | | C un |
| D29 • f. | Bare Board | | <u> </u> |
| | \$0.00 Fix | tures/ SAVE/COMPARE | 1 |
| Bare Board Design Assistant | \$0.00 Refail | 9 | П. |
| Monitor \$5 Z00M | | | |
| Select Ounces of Flished Copper (Outer Layers) Select Ounces of Copper (Inner Layers) Select Surface Finish over Copper | 1/1 0.500/0.500 HASL (Hot Air Solder Levaled) | 3,1:1 Aspect Ratio | |
| Min. Finished Plated Through Hole (Outer Layer) Plated Thru Hole Prep Min. Finished Plated Through Hole (Inner Layer) Maximum Finished Plated Through Hole (Inches) | 6.0197 0.037 < Min. standard >=.003 < Outer 0.0197 0.037 < Min. 0.060 >=.002 < Inner | Kin. Pad Sjae (Outer) Outer Loyer Hole Tolerance Kin. Pad Size (Inner) Kin. Pad Size (Inner) Kiner Loyer Hole Tolerance | |
| Enter Total # Drilled Holes / Board Annular Are there any Plated Stote? Ring Example | ← Holes | Holes < or=0.020° ° | |
| Are there any Man-Plated Slots? 214 | 88 0002 | | |
| Select Minimum Outer Layer Trace (Inches) | 0.007 0.007 < Outer | < Outer Layer Space | |
| Select Minimum Inner Layer Trace (Inches) Inner Layer Trace Tolerance Inner Layer Trace Tolerance | 0.007 | < Inner Layer Space Inner Trace/Space-Good Registration-Good | |
| Solder Mask Needed? | Yes Green < Solde | < Soider Nask Calar | • |
| | | | • |
| • | | 60 Internet | ± |
| (<i>Bstart</i>) Bare Board Design | | | ₩A81:9 🗞 🕏 🕏 |
| | | | |

Fig. 7



| 🕙 Bare Board Design Assistant – Microsoft Internet Explorer | XD- |
|--|------------------|
| File Edit View Fovorites Tools Help | \mathcal{B} |
| ← Back - → X Z ← X Z Foworlies ← Media ← Ø 🖄 ♣ 🖼 - 🔲 Links | |
| Address | °5 1 ∧ |
| | |
| Design Assistant Tools | < m |
| Bare Board | <u>D</u> |
| SAVE / COMPARE | - |
| \$0.00 Retail Price/ | |
| 3 Option | 7 |
| Select Ounces of Finished Copper (Ouler Layers) 1/1 3.1:1 Aspect Ratio Select Ounces of Copper (Inner Layers) 0.500/0.500 Select Surface Finish over Copper HASI (Hat Air Solder Leveled) | |
| Min. Finlahed Ploted Through Hole (Outer Layer) Ploted Thru Hole Prep Min. Finlahed Ploted Chrough Hole (Inner Layer) Standard S=.0037 Suite Layer Hole Couter Court | nn |
| rough Hole State / Board Annular Was (f State) • Kommole / Commole Foundation / Commole / Commo | |
| ots? | |
| Select Minimum Outer Layer Trace (Inches) 9 0,007 0,007 0,007 c Outer Layer Space | |
| Trace (inches) 0.007 | |
| \$ P | • |
| • | • |
| ₿ Done | Ø Internet |
| (Bstart) 🗗 Bare Board Design | WA81:9 🗞 🖒 🕏 🗓 |
| | |

Fig. 8







Fig. 9






Fig. 10






Fig. 11




Fig. 12






Fig. 13






Fig. 14

B **⊘⊗** 10:17AM ვ **1** Unknown Zone > 0+ 🖻 6 Clear 3 1,986.23 62.22 0.500/0.500 HASL (Hot Air Solder Leveled) Mull Layer - 4L FR4, M/L, 175 Tg nam. 0.062 | +/-1 232 Option 3 Tooling Retail Price/ Board 다ks Fixtures, -228 Clear 2 1,812.10 B 40.41 HASL (Hot Air Solder Leveled) 232 Option 2 Retail Price/ Board Tooling Fixtures , 0.00 Media Clear 1 ර 1,912.10 50.53 HASL (Hot Air Solder Leveled) 0.00 \$\frac{1}{2}\text{Favorites} 🔁 Bare Board Design Assistant – Microsoft Internet Explorer Option 1 Bare Board Design (Assistant Retail Price)

Board Fixtures / Search 0.007 Board/Array Dimensions
X-Outs Permitted / Profile Tolerance
Menulacturing Panel Ullization X (Calculated)
Number of Boards Vibration / Y Direction
Board Step
Enter Quantity
Turnoraud Required
Type of Board Thickness (Inches)/Tolerance
Laminate Material
Tolerance of Capper (Outer Layers)
Ounces of Capper (Inner Layers)
Surface Finish over Capper
Min. Finished Pitted Thru Hole / Pad (Inner
Mar Finished Pitted Thru Hole / Pad (Inner
Mar Finished Pitted Thru Hole / Pad (Inner
Mar Finished Pitted Mary / Inner Hole Tolerance
Enter Total & Different Thru Hole Sizes
Total & Different Size & / Lacetions
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & / Width of Size & /
Length of Size & Bare Board Design... 물 Clear All \$ Single Board or Multi-Board Array / # per

泛 (·) × Favorites

Ē Back

Ē

٠ **①** View

PRINT

RETURN

22

Address

Bstart